



STORAGE AND HANDLING GUIDELINES FOR ThermaCalWALL INSULATION

Note: The following information is based upon PIMA Technical Bulletin #109 and the guidelines set forth in the Cornell Corporation “Terms and Conditions” document.

STORAGE:

1. Cornell Corporation's products are shipped covered with a plastic bag which is intended to temporarily protect the material while in transit only.
2. Material delivery and shipment dates are the responsibility of the customer and should be coordinated with the installation schedule to minimize job site storage.
3. If jobsite storage is necessary, observe the following precautions.
 - a) Place the package of material well above the ground level. (Minimum of 4”).
 - b) Storage area should be flat and dry and adequate drainage to keep product free from moisture.
 - c) Storage area should be a finished area, not dirt or grass.
 - d) Cover the material with a breathable waterproof tarpaulin. The plastic cover bag from the factory should not be relied upon for job site protection and should be removed or cut open if moisture accumulates inside of it.
 - e) Adequate precautions against rodent and other animal damage should be taken.
 - f) Long-term job site storage is not recommended. If the product is going to be stored for more than 2 weeks prior to installation, it is recommended that it be stored indoors inside of a dry, temperature-controlled, well ventilated warehouse.
 - g) Cornell Corporation is not responsible for dimensional changes or damage issues related to improper extended storage.

HANDLING:

Use care when handling nail board products to prevent breaking or crushing of the corners. Remove the product from the truck using proper equipment.

PRODUCT APPLICATION:

Nail board should always be installed on dry, clean wall surfaces in dry conditions. Follow our installation directions regarding product application. Apply only as much product to the wall as can be covered in one day. Any insulation that becomes wet must be replaced with solid, dry insulation.

SAFETY:

Foam insulation board like other building materials is combustible so it must not be exposed to any ignition sources (flames, fire, sparks, light bulbs, etc.), during transit, storage or product application. Follow all regulations from OSHA, NFPA and local fire authorities.